

Vaisala Radiosonde RS41-SG

Temperature and Humidity Sensors

The Vaisala Radiosonde RS41 temperature sensor is very stable utilizing linear resistive platinum technology. The small size of the sensor results in low solar radiation error and guarantees fast response.

The Vaisala Radiosonde RS41 humidity sensor integrates humidity and temperature sensing elements to provide unique features. Prior flight automatic recondition of the humidity sensor effectively removes chemical contaminants and ensures excellent humidity measurement accuracy. Integrated temperature sensor is used to compensate the effects of solar radiation in real time resulting in very precise measurement. The humidity sensor is very accurate throughout the whole measurement range and has fast response to detect fine structures of the atmosphere.

RS41 Ground Check

RS41 ground check includes several functional checks: temperature check, humidity sensor recondition, humidity check and setting radiosonde parameters. Ground check is performed prior to flight for a radiosonde placed on the MW41 operated device, either Ground Check Device RI41 or optional GC41.

Both ground check devices are conveniently operated with MW41 software. Short range wireless communication link is used in ground check devices for turning radiosonde power on and for data transfer during the ground check. The communication link is based on the RF technique within the range around 4 cm.

In addition to several smart electrical checks the temperature element of the humidity sensor is used to accomplish check against RS41 temperature sensor giving additional confidence and redundancy for functional check during in-built functional temperature check.

Utilizing the new humidity sensor design, the radiosonde is able to generate physical dry humidity reference more consistently than is possible with desiccants. The sensor can measure the deviation of humidity measurement at 0 %RH (physical zero) and fine tune the humidity measurement accordingly.

External References Option

The optional Vaisala Ground Check Device GC41 has a measurement chamber and reference for temperature and optionally also desiccants to create non-humid conditions to be used as humidity reference.

Whether the RI41 or the GC41 device is used in ground check the end result and measurement accuracy in sounding is the same. For its simplicity RI41 is the recommended device for RS41 ground check. As an option, GC41 with external temperature reference and desiccants can be used, but with RS41 they are not needed to ensure the specified measurement accuracy.

Wind data, height and pressure

Wind data, height and pressure are derived from the Vaisala Radiosonde RS41-SG GPS data combined with differential corrected GPS data from the MW41 ground station.

Data transmission

The Vaisala Radiosonde RS41-SG has proven data transmission from radiosonde to receiver up to 350 km. This is sufficient for any sounding operations. Data availability during a sounding is guaranteed with digital error correction code transmission and telemetry errors are always detected. Due to narrow band transmission more channels are available in the meteorological frequency band.

The Vaisala Radiosonde RS41-SG is fully compliant with the European ETSI standard for radiosondes operating in the 400 MHz band, EN 302 054.

RS41 Calibration

The Vaisala Radiosonde RS41's temperature and humidity sensors are calibrated against the references that are traceable to SI standards.

Operational benefits

The RS41's robust and compact design makes it easy to handle during launch preparations. There is no assembly needed prior to launch.



Vaisala Radiosonde RS41-SG – accuracy and reliability.

Benefits

- Superior PTU measurement performance
- Automated ground check
- Robust and easy to use design
- GPS for continuous wind data availability as well as height and pressure calculation
- Stable narrow band transmission complies with ETSI standard EN 302 054

The status LED indicates when the RS41 is ready to launch, and if there is an error, it is clearly indicated prior to launch.

Unwinder

With the unwinder the radiosonde sensor boom is automatically set in an ideal position for sounding. As the unwinder is separated from the radiosonde, the balloon and unwinder can be prepared in advance to streamline launch preparations.

Technical Data

Measurements

Measurement cycle	1 s
TEMPERATURE SENSOR	TYPE: PLATINUM RESISTOR
Measurement range	+60 °C to -90 °C
Resolution	0.01 °C
Response time (63.2%, 6 m/s flow, 1000 hPa)	0.5 s
Stability (0.5 year)	0.05 °C
Accuracy	
Repeatability in calibration	0.1 °C
Combined uncertainty after ground preparation	0.2 °C
Combined uncertainty in sounding <16 km	0.3 °C
Combined uncertainty in sounding >16 km	0.4 °C
Reproducibility in sounding > 100 hPa ¹	0.15 °C
< 100 hPa ¹	0.30 °C

HUMIDITY SENSOR	TYPE: THIN-FILM CAPACITOR
Measurement range	0 to 100 %RH
Resolution	0.1 %RH
Response time	
6 m/s, 1000 hPa, +20 °C	< 0.3 s
6 m/s, 1000 hPa, -40 °C	< 10 s
Accuracy	
Repeatability in calibration	2 %RH
Combined uncertainty after ground preparation	3 %RH
Combined uncertainty in sounding	4 %RH
Reproducibility in sounding ¹	2 %RH

PRESSURE	TYPE: Calculated from GPS
Measurement range	from surface pressure to 3 hPa
Resolution	0.01 hPa
Accuracy	
Combined uncertainty/ Reproducibility ¹ in sounding	
> 100 hPa	1.0 hPa / 0.5 hPa
100 - 10 hPa	0.3 hPa / 0.2 hPa
<10 hPa	0.04 hPa / 0.04 hPa

GEOPOTENTIAL HEIGHT	TYPE: Calculated from GPS
Measurement range ²	from surface to 40000 m
Resolution	0.1 gpm
Accuracy	
Combined uncertainty in sounding	10.0 gpm
Reproducibility in sounding ¹	6.0 gpm

WIND SPEED	
Velocity measurement uncertainty ³	0.15 m/s
Resolution	0.1 m/s
Maximum reported wind speed ²	160 m/s

WIND DIRECTION	
Directional measurement uncertainty ³	2 deg
Resolution	0.1 deg
Wind direction range	0 to 360 deg

Telemetry

Transmitter type	Synthesized
Tuning range	400.15 – 405.99 MHz
Maximum transmitting range	up to 350 km
Frequency stability, 90 % probability	± 2 kHz
Deviation, peak-to-peak	4.8 kHz
Emission bandwidth	According to EN 302 054
Output power (high-power mode)	min. 60 mW
Sideband radiation	According to EN 302054
Modulation	GFSK
Data downlink	4800 bit/s
Frequency setting	Wireless with RI41/GC41

GPS receiver (SA Off, PDOP<4)

Number of channels	≥ 48
Frequency	1575.42 MHz, L1 C/A code
Cold Start Acquisition Time	35 s (nominal)
Reacquisition Time	1 s (nominal)
Correction	Differential
Reporting resolution of lat, lon position values	1e-8°

Operational Data

Power-up	Wireless with RI41/GC41 or with switch
Factory calibration	Stored on Flash memory
Battery	2 pcs AA-size Lithium cells
Operating time	> 240 min
Weight ⁴	109 g
Dimensions ⁵	Body (L x W x H): 145 x 63 x 46 mm
	Sensor boom bent (L x W x H): 272 x 63 x 104 mm

Unwinder

Material of the string	Non-UV treated polypropylene
Tenacity	<115 N
Length of the string	30 m
Unwinding speed	0.35 m/s
Weight	20 g

The performance data is expressed with 2-sigma confidence level (k=2), if not otherwise specified, for humidity T > -60 °C

- 1) Standard deviation of differences in twin soundings, ascent rate above 3 m/s
- 2) In practice unlimited
- 3) Standard deviation of differences in twin soundings. Wind speed above 3 m/s for directional measurement uncertainty.
- 4) Weight with unwinder 129 g + rigging, parachute, etc.
- 5) Without wire antenna

VAISALA

For more information, visit
www.vaisala.com or contact
 us at sales@vaisala.com

Ref. B211321EN-A ©Vaisala 2013

This material is subject to copyright protection, with all copyrights retained by Vaisala and its individual partners. All rights reserved. Any logos and/or product names are trademarks of Vaisala or its individual partners. The reproduction, transfer, distribution or storage of information contained in this brochure in any form without the prior written consent of Vaisala is strictly prohibited. All specifications — technical included — are subject to change without notice.

